

Description

Fastener Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470D614
Minimum Qty (MOQ):	255 EA
NSN:	5320-01-058-3383
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20470D6-14 Specifications

Fastener Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Shear Strength:	33000 Single Pounds Per Square Inch
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470D6-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.