

# P/N MS20470D6-4

### **Description**

length: 1/4", diameter: 3/16", universal head, 2017-t4 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

| SKU / Model:            | MS20470D64         |
|-------------------------|--------------------|
| Minimum Qty (MOQ):      | 1 Pound            |
| NSN:                    | 5320-00-839-5834   |
| ECCN:                   | EAR99              |
| National Motor Freight: | 013630 Alum Rivets |



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470D6-4 Specifications

| Fastener Length:     | 0.240 Inches Minimum And 0.260 Inches Maximum |
|----------------------|---|
| Head Style:          | Universal                                     |
| Head Height:         | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter:      | 0.186 Inches Minimum And 0.191 Inches Maximum |
| Shank Style:         | Straight                                      |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Material:            | Aluminum Alloy 1100 Overall                   |
| Surface Treatment:   | Anodize Overall                               |

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470D6-4">https://military-fasteners.com/rivets/solid+rivets/MS20470D6-4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.