

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470D713
Minimum Qty (MOQ):	115 EA
NSN:	5320-00-324-9724
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20470D7-13 Specifications

Fastener Length:	0.812 Inches Nominal
Head Style:	Universal
Head Height:	0.093 Inches Minimum And 0.103 Inches Maximum
Shank Diameter:	0.218 Inches Minimum And 0.223 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.415 Inches Minimum And 0.459 Inches Maximum
Shear Strength:	33000 Single Pounds Per Square Inch
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470D7-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.