

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470D716 |
| Minimum Qty (MOQ): | 170 EA |
| NSN: | 5320-00-323-4573 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20470D7-16 Specifications

| | |
|---|--|
| Fastener Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.093 Inches Minimum And 0.103 Inches Maximum |
| Shank Diameter: | 0.218 Inches Minimum And 0.223 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.415 Inches Minimum And 0.459 Inches Maximum |
| Shear Strength: | 33000 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Qq-a-430,t4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470D7-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.