

Description

Fastener Length: 31/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470DD6155
Minimum Qty (MOQ):	335 EA
NSN:	5320-00-170-3669
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20470DD6-15-5 Specifications

Fastener Length:	0.959 Inches Minimum And 0.979 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Shear Strength:	37000 Single Pounds Per Square Inch
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470DD6-15-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.