

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470DD87
Minimum Qty (MOQ):	130 EA
NSN:	5320-00-119-6763
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20470DD8-7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.254 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Grip Length:	0.053 Inches Minimum And 0.073 Inches Maximum
Shear Strength:	37000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470DD8-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.