

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470DD89
Minimum Qty (MOQ):	200 EA
NSN:	5320-00-117-6535
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N MS20470DD8-9 Specifications

<b>Fastener Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.107 Inches Minimum And 0.117 Inches Maximum
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.254 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.475 Inches Minimum And 0.525 Inches Maximum
<b>Grip Length:</b>	0.177 Inches Minimum And 0.197 Inches Maximum
<b>Shear Strength:</b>	37000 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470DD8-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.