

**Description**

Fastener Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470E1014
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-307-4601
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20470E10-14 Specifications

<b>Identification Code Color:</b>	Yellow
<b>Fastener Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.133 Inches Minimum And 0.143 Inches Maximum
<b>Shank Diameter:</b>	0.311 Inches Minimum And 0.316 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.594 Inches Minimum And 0.656 Inches Maximum
<b>Shear Strength:</b>	41000 Single Pounds Per Square Inch
<b>Special Features:</b>	Aluminum Alloy 7050
<b>Heat Treatment:</b>	T-73 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E10-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.