

Description

Fastener Length: 1/2", universal head, roughly 140 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E108
Minimum Qty (MOQ):	1000
NSN:	5320-01-236-2981
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N MS20470E10-8 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Universal
Head Height:	0.133 Inches Minimum And 0.143 Inches Maximum
Shank Diameter:	0.311 Inches Minimum And 0.316 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.594 Inches Minimum And 0.656 Inches Maximum
Shear Strength:	41000 Single Pounds Per Square Inch
Special Features:	Aluminum Alloy 7050
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E10-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.