

Description

Fastener Length: 1/2", universal head, roughly 140 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS20470E108 |
| Minimum Qty (MOQ): | 1000 |
| NSN: | 5320-01-236-2981 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS20470E10-8 Specifications

| | |
|---|---|
| Identification Code Color: | Yellow |
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.133 Inches Minimum And 0.143 Inches Maximum |
| Shank Diameter: | 0.311 Inches Minimum And 0.316 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.594 Inches Minimum And 0.656 Inches Maximum |
| Shear Strength: | 41000 Single Pounds Per Square Inch |
| Special Features: | Aluminum Alloy 7050 |
| Heat Treatment: | T-73 Solution Heat Treated Overall |
| Material: | Aluminum Alloy Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E10-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.