

Description

Fastener Length: 63/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E216
Minimum Qty (MOQ):	1000
NSN:	5320-01-307-4705
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N MS20470E2-16 Specifications

<b>Identification Code Color:</b>	Yellow
<b>Fastener Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.027 Inches Minimum And 0.037 Inches Maximum
<b>Shank Diameter:</b>	0.061 Inches Minimum And 0.065 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.119 Inches Minimum And 0.131 Inches Maximum
<b>Shear Strength:</b>	41000 Single Pounds Per Square Inch
<b>Special Features:</b>	Aluminum Alloy 7050
<b>Heat Treatment:</b>	T-73 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E2-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.