

**Description**

Fastener Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20470E312                                 |
| Minimum Qty (MOQ):      | 505 EA                                      |
| NSN:                    | 5320-01-307-4698                            |
| Schedule B:             | 7616.10.3000                                |
| ECCN:                   | 9A991                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20470E3-12 Specifications

|   |  |
|---|--|
| <b>Identification Code Color:</b>                     | Yellow   |
| <b>Fastener Length:</b>                               | 0.740 Inches Minimum And 0.760 Inches Maximum                |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.040 Inches Minimum And 0.050 Inches Maximum                |
| <b>Shank Diameter:</b>                                | 0.093 Inches Minimum And 0.097 Inches Maximum                |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip                              |
| <b>Head Major Diameter:</b>                           | 0.178 Inches Minimum And 0.196 Inches Maximum                |
| <b>Shear Strength:</b>                                | 41000 Single Pounds Per Square Inch                          |
| <b>Heat Treatment:</b>                                | T-73 Solution Heat Treated Overall                           |
| <b>Material:</b>                                      | Aluminum Alloy Overall                                       |
| <b>Material Document And Classification:</b>          | Qq-a-430 Comp 7050 Fed Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall  |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E3-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.