

## P/N MS20470E3-16A

### **Description**

Fastener Length: 0-63/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS20470E316A

Minimum Qty (MOQ): 1000 EA

NSN: 5320-01-397-5104

Schedule B: 7616.10.3000

ECCN: 9A991

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470E3-16A Specifications

Fastener Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470E3-16A">https://military-fasteners.com/rivets/solid+rivets/MS20470E3-16A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.