

# P/N MS20470E3-8A

### **Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS20470E38A
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-359-6975
Schedule B:	7616.10.3000
FCCN:	94991



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470E3-8A Specifications

Fastener Length:	0.5000 Inches Minimum And 0.5100 Inches Maximum
Head Style:	Universal
Head Height:	0.0400 Inches Minimum And 0.0500 Inches Maximum
Shank Diameter:	0.0930 Inches Minimum And 0.0970 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1780 Inches Minimum And 0.1960 Inches Maximum
Material:	Aluminum Alloy 7050 Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470E3-8A">https://military-fasteners.com/rivets/solid+rivets/MS20470E3-8A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470E3-8A">https://military-fasteners.com/rivets/solid+rivets/MS20470E3-8A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470E3-8A">https://military-fasteners.com/rivets/solid+rivets/MS20470E3-8A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470E3-8A">https://military-fasteners.com/rivets/solid+rivets/MS20470E3-8A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/ms20470E3-8A">https://military-fasteners.com/rivets/solid+rivets/ms20470E3-8A</a> and selecting the quantity you want then cart in the property of the proper