

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470E43A |
| Minimum Qty (MOQ): | 505 EA |
| NSN: | 5320-01-276-4905 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20470E4-3A Specifications

| | |
|---|---|
| Fastener Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Shear Strength: | 41000 Single Pounds Per Square Inch |
| Heat Treatment: | T-3 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7050 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E4-3A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.