

# P/N MS20470E4-5A-5

### **Description**

Fastener Length: 5/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS20470E45A5

Minimum Qty (MOQ): 255 EA

NSN: 5320-01-542-3310

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

## P/N MS20470E4-5A-5 Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.640 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet, Solid, Universal Head
Material:	Aluminum Alloy 7050 Overall
Surface Treatment:	Anodize Overall

### **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470E4-5A-5">https://military-fasteners.com/rivets/solid+rivets/MS20470E4-5A-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.