

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS20470E510A |
| Minimum Qty (MOQ): | 255 EA |
| NSN: | 5320-01-542-7344 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS20470E5-10A Specifications

| | |
|---|--|
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Brazier |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.312 Inches Nominal |
| Part Name Assigned By Controlling Agency: | Rivet, Solid, Universal Head |
| Special Features: | Rivet Head Has An Indented Ring Maximum Of 75% Of Rivet Shank Diameter (0.156 Nominal Dia.), Max Depth Of 0.010 Inch |
| Material: | Aluminum Alloy Overall |
| Material Document And Classification: | 7050-t73 Al Alloy National Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Cl 1a Clear Or Gold/yellow Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E5-10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.