

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E510A
Minimum Qty (MOQ):	255 EA
NSN:	5320-01-542-7344
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20470E5-10A Specifications

Fastener Length:	0.625 Inches Nominal
Head Style:	Brazier
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.312 Inches Nominal
Part Name Assigned By Controlling Agency:	Rivet, Solid, Universal Head
Special Features:	Rivet Head Has An Indented Ring Maximum Of 75% Of Rivet Shank Diameter (0.156 Nominal Dia.), Max Depth Of 0.010 Inch
Material:	Aluminum Alloy Overall
Material Document And Classification:	7050-t73 Al Alloy National Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Cl 1a Clear Or Gold/yellow Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E5-10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.