

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470E510A
Minimum Qty (MOQ):	255 EA
NSN:	5320-01-542-7344
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20470E5-10A Specifications

<b>Fastener Length:</b>	0.625 Inches Nominal
<b>Head Style:</b>	Brazier
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.312 Inches Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, Solid, Universal Head
<b>Special Features:</b>	Rivet Head Has An Indented Ring Maximum Of 75% Of Rivet Shank Diameter (0.156 Nominal Dia.), Max Depth Of 0.010 Inch
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	7050-t73 Al Alloy National Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Cl 1a Clear Or Gold/yellow Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E5-10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.