

Description

length: 3/4", diameter: 5/32", universal head, aluminum alloy, approximately 550 pieces per pound, MS20470 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN470E5-12](#)

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470E512 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-01-256-2605 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20470E5-12 Specifications

| | |
|---|---|
| Identification Code Color: | Yellow |
| Fastener Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.160 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Shear Strength: | 41000 Single Pounds Per Square Inch |
| Special Features: | Aluminum Alloy 7050 |
| Heat Treatment: | T-73 Solution Heat Treated Overall |
| Material: | Aluminum Alloy Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E5-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.