

Description

Fastener Length: 3/4, roughly 525 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E513
Minimum Qty (MOQ):	250
NSN:	5320-01-484-7574
Schedule B:	7616.10.3000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS20470E5-13 Specifications

Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Brazier
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Straight W/chamfered Tip
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet, Solid, Universal Head
Material:	Aluminum Alloy 7050 Overall
Surface Treatment Document And Classification:	Mil-c-5541, Class 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E5-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.