

Description

Fastener Length: 1-3/4, roughly 270 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E528
Minimum Qty (MOQ):	100
NSN:	5320-01-219-5738
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20470E5-28 Specifications

Identification Code Color:	Yellow
Fastener Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Shear Strength:	41000 Single Pounds Per Square Inch
Special Features:	Aluminum Alloy 7050
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E5-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.