

**Description**

Fastener Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20470E57S                                 |
| Minimum Qty (MOQ):      | 335 EA                                      |
| NSN:                    | 5320-01-591-8883                            |
| Schedule B:             | 7616.10.3000                                |
| ECCN:                   | 9A991                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N MS20470E5-7S Specifications

|                             |   |
|-----------------------------|---|
| <b>Fastener Length:</b>     | 0.428 Inches Minimum And 0.448 Inches Maximum |
| <b>Head Style:</b>          | Universal                                     |
| <b>Head Height:</b>         | 0.067 Inches Minimum And 0.077 Inches Maximum |
| <b>Shank Diameter:</b>      | 0.155 Inches Minimum And 0.159 Inches Maximum |
| <b>Shank Style:</b>         | Straight W/radius Chamfered Tip               |
| <b>Head Major Diameter:</b> | 0.296 Inches Minimum And 0.328 Inches Maximum |
| <b>Material:</b>            | Aluminum Alloy 7050 Overall                   |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E5-7S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.