

**Description**

Length: 3/4", diameter: 3/16", universal head, 7050-t73 aluminum alloy, roughly 550 pieces per pound, MS20470 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20470E612         |
| Minimum Qty (MOQ):      | 1 Pound             |
| NSN:                    | 5320-01-289-6074    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N MS20470E6-12 Specifications

|   |  |
|---|--|
| <b>Identification Code Color:</b>                     | Yellow   |
| <b>Fastener Length:</b>                               | 0.740 Inches Minimum And 0.760 Inches Maximum                |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.080 Inches Minimum And 0.090 Inches Maximum                |
| <b>Shank Diameter:</b>                                | 0.186 Inches Minimum And 0.191 Inches Maximum                |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip                              |
| <b>Head Major Diameter:</b>                           | 0.356 Inches Minimum And 0.394 Inches Maximum                |
| <b>Shear Strength:</b>                                | 41000 Single Pounds Per Square Inch                          |
| <b>Heat Treatment:</b>                                | T-73 Solution Heat Treated Overall                           |
| <b>Material:</b>                                      | Aluminum Alloy Overall                                       |
| <b>Material Document And Classification:</b>          | Qq-a-430 Comp 7050 Fed Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall  |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.