

Description

Fastener Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470E62
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-390-7112
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20470E6-2 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.114 Inches Minimum And 0.134 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Shear Strength:	41000 Single Pounds Per Square Inch
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541, Cl 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E6-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.