

Description

Fastener Length: 1-3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS20470E622 |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5320-01-307-4690 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20470E6-22 Specifications

| | |
|---|--|
| Identification Code Color: | Yellow |
| Fastener Length: | 1.365 Inches Minimum And 1.385 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.191 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Shear Strength: | 41000 Single Pounds Per Square Inch |
| Heat Treatment: | T-73 Solution Heat Treated Overall |
| Material: | Aluminum Alloy Overall |
| Material Document And Classification: | Qq-a-430 Comp 7050 Fed Spec Single Material Response Overall |
| Surface Treatment: | Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E6-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.