

Description

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E66S
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-360-1779
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N MS20470E6-6S Specifications

<b>Fastener Length:</b>	0.3650 Inches Minimum And 0.3850 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.0800 Inches Minimum And 0.0900 Inches Maximum
<b>Shank Diameter:</b>	0.1860 Inches Minimum And 0.1900 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.3560 Inches Minimum And 0.3940 Inches Maximum
<b>Material:</b>	Aluminum Alloy 7050 Overall
<b>Surface Treatment:</b>	Chromate Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E6-6S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.