

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E66S
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-360-1779
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS20470E6-6S Specifications

Fastener Length:	0.3650 Inches Minimum And 0.3850 Inches Maximum
Head Style:	Universal
Head Height:	0.0800 Inches Minimum And 0.0900 Inches Maximum
Shank Diameter:	0.1860 Inches Minimum And 0.1900 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.3560 Inches Minimum And 0.3940 Inches Maximum
Material:	Aluminum Alloy 7050 Overall
Surface Treatment:	Chromate Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E6-6S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.