

**Description**

Fastener Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470E69S
Minimum Qty (MOQ):	60 EA
NSN:	5320-01-360-1780
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N MS20470E6-9S Specifications

<b>Fastener Length:</b>	0.5625 Inches Minimum And 0.5725 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.0540 Inches Minimum And 0.0640 Inches Maximum
<b>Shank Diameter:</b>	0.1240 Inches Minimum And 0.1280 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.2380 Inches Minimum And 0.2620 Inches Maximum
<b>Material:</b>	Aluminum Alloy 7050 Overall
<b>Surface Treatment:</b>	Chromate Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E6-9S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.