

P/N MS20470E6-9S

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E69S
Minimum Qty (MOQ):	60 EA
NSN:	5320-01-360-1780
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N MS20470E6-9S Specifications

Fastener Length:	0.5625 Inches Minimum And 0.5725 Inches Maximum
Head Style:	Universal
Head Height:	0.0540 Inches Minimum And 0.0640 Inches Maximum
Shank Diameter:	0.1240 Inches Minimum And 0.1280 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2380 Inches Minimum And 0.2620 Inches Maximum
Material:	Aluminum Alloy 7050 Overall
Surface Treatment:	Chromate Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20470E6-95 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20470E6-95 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20470E6-95 and selecting the quantity you want then click "add to cart".