

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470E79
Minimum Qty (MOQ):	200 EA
NSN:	5320-01-434-2972
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N MS20470E7-9 Specifications

Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Universal
Head Height:	0.093 Inches Minimum And 0.103 Inches Maximum
Shank Diameter:	0.218 Inches Minimum And 0.222 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.415 Inches Minimum And 0.459 Inches Maximum
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541, Class 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E7-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.