

## Description

Solid Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS20470E811
Minimum Qty (MOQ):	115 EA
NSN:	5320-01-468-1185
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N MS20470E8-11 Specifications

<b>Fastener Length:</b>	0.688 Inches Nominal
<b>Head Style:</b>	Oval/truss
<b>Head Height:</b>	0.107 Inches Minimum And 0.117 Inches Maximum
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.253 Inches Maximum
<b>Shank Style:</b>	Straight W/chamfered Tip
<b>Head Major Diameter:</b>	0.475 Inches Minimum And 0.525 Inches Maximum
<b>End Item Identification:</b>	C-17a Aircraft
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, Solid-universal Head
<b>Special Features:</b>	4surface Texture 125 Microinches Per Ansi B46.1-78;deburr And Break All Edges .005-.015;rivets May Be Furnished With Plain Ends,end Chamferred 20 Degrees To The H Dimension, Or May Have A Radius Per The T Dimension;dimensions Apply After Coating
<b>Material:</b>	Aluminum Alloy 7050 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall And Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type1,class1 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E8-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.