

Description

Solid Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470E811
Minimum Qty (MOQ):	115 EA
NSN:	5320-01-468-1185
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N MS20470E8-11 Specifications

Fastener Length:	0.688 Inches Nominal
Head Style:	Oval/truss
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Straight W/chamfered Tip
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
End Item Identification:	C-17a Aircraft
Part Name Assigned By Controlling Agency:	Rivet, Solid-universal Head
Special Features:	4surface Texture 125 Microinches Per Ansi B46.1-78;deburr And Break All Edges .005-.015;rivets May Be Furnished With Plain Ends,end Chamferred 20 Degrees To The H Dimension, Or May Have A Radius Per The T Dimension;dimensions Apply After Coating
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall And Aluminum Overall
Surface Treatment Document And Classification:	Mil-a-8625,type1,class1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E8-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.