

Description

Fastener Length: 3/4", roughly 185 pieces per pound, MS20470 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E812
Minimum Qty (MOQ):	100
NSN:	5320-01-223-1776
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS20470E8-12 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.254 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Shear Strength:	41000 Single Pounds Per Square Inch
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-430 Comp 7050 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541 Cl 1a Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E8-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.