

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470E87A
Minimum Qty (MOQ):	115 EA
NSN:	5320-01-424-9575
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20470E8-7A Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type II, Class 1, Clear Mil Spec Single Treatment Response Overall
Specification/standard Data:	96906-ms20470 Government Specification

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E8-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.