

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS20470E87A |
| Minimum Qty (MOQ): | 115 EA |
| NSN: | 5320-01-424-9575 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N MS20470E8-7A Specifications

| | |
|---|--|
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.107 Inches Minimum And 0.117 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.253 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.475 Inches Minimum And 0.525 Inches Maximum |
| Heat Treatment: | T-73 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Type II, Class 1, Clear Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 96906-ms20470 Government Specification |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470E8-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.