

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470T23
Minimum Qty (MOQ):	500 EA
NSN:	5320-01-467-5403
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20470T2-3 Specifications

Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Universal
Head Height:	0.027 Inches Minimum And 0.037 Inches Maximum
Shank Diameter:	0.061 Inches Minimum And 0.065 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.119 Inches Minimum And 0.131 Inches Maximum
Grip Length:	0.084 Inches Minimum And 0.104 Inches Maximum
Material:	Titanium Alloy Uns R58450 Overall
Material Document And Classification:	Ams 4982 National Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T2-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.