

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470T37
Minimum Qty (MOQ):	145 EA
NSN:	5320-01-359-6977
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N MS20470T3-7 Specifications

Fastener Length:	0.4280 Inches Minimum And 0.4480 Inches Maximum
Head Style:	Universal
Head Height:	0.0400 Inches Minimum And 0.0500 Inches Maximum
Shank Diameter:	0.0920 Inches Minimum And 0.0970 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1780 Inches Minimum And 0.1960 Inches Maximum
Material:	Titanium Alloy Uns R58450 Overall
Material Document And Classification:	Ams 4982 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T3-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.