

**Description**

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | MS20470T510                          |
| Minimum Qty (MOQ):      | 10                                   |
| NSN:                    | 5320-00-170-3455                     |
| ECCN:                   | EAR99                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



## P/N MS20470T5-10 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.615 Inches Minimum And 0.635 Inches Maximum            |
| <b>Head Style:</b>                           | Universal  |
| <b>Head Height:</b>                          | 0.067 Inches Minimum And 0.077 Inches Maximum            |
| <b>Shank Diameter:</b>                       | 0.155 Inches Minimum And 0.159 Inches Maximum            |
| <b>Shank Style:</b>                          | Straight   |
| <b>Head Major Diameter:</b>                  | 0.296 Inches Minimum And 0.328 Inches Maximum            |
| <b>Shear Strength:</b>                       | 50000 Single Pounds Per Square Inch                      |
| <b>Heat Treatment:</b>                       | Annealed Overall   |
| <b>Material:</b>                             | Titanium Alloy Overall                                   |
| <b>Material Document And Classification:</b> | -172,fscm 11815 Mfr Ref Single Material Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.