

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20470T511                                 |
| Minimum Qty (MOQ):      | 15 EA                                       |
| NSN:                    | 5320-01-259-6397                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N MS20470T5-11 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.677 Inches Minimum And 0.697 Inches Maximum      |
| <b>Head Style:</b>                           | Universal  |
| <b>Head Height:</b>                          | 0.067 Inches Minimum And 0.077 Inches Maximum      |
| <b>Shank Diameter:</b>                       | 0.155 Inches Minimum And 0.160 Inches Maximum      |
| <b>Shank Style:</b>                          | Straight W/radius Chamfered Tip                    |
| <b>Head Major Diameter:</b>                  | 0.296 Inches Minimum And 0.328 Inches Maximum      |
| <b>Shear Strength:</b>                       | 50000 Single Pounds Per Square Inch                |
| <b>Heat Treatment:</b>                       | Annealed Overall                                   |
| <b>Material:</b>                             | Titanium Alloy Uns R58450 Overall                  |
| <b>Material Document And Classification:</b> | Ams 4982 Assn Std Single Material Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T5-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.