

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | MS20470T512 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-00-170-3474 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N MS20470T5-12 Specifications

| | |
|--|--|
| Fastener Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Shear Strength: | 50000 Single Pounds Per Square Inch |
| Heat Treatment: | Annealed Overall |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | -172,fscm 11815 Mfr Ref Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T5-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.