

# P/N MS20470T5-6-5

### **Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS20470T565

Minimum Qty (MOQ): 20 EA

NSN: 5320-01-027-4714

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470T5-6-5 Specifications

Fastener Length:	0.396 Inches Minimum And 0.416 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4982 Columbium Alloy Assn Std Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470T5-6-5">https://military-fasteners.com/rivets/solid+rivets/MS20470T5-6-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.