

**Description**

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20470T58                                  |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5320-01-238-8911                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



## P/N MS20470T5-8 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.490 Inches Minimum And 0.510 Inches Maximum      |
| <b>Head Style:</b>                           | Universal  |
| <b>Head Height:</b>                          | 0.067 Inches Minimum And 0.077 Inches Maximum      |
| <b>Shank Diameter:</b>                       | 0.155 Inches Minimum And 0.160 Inches Maximum      |
| <b>Shank Style:</b>                          | Straight W/radius Chamfered Tip                    |
| <b>Head Major Diameter:</b>                  | 0.296 Inches Minimum And 0.328 Inches Maximum      |
| <b>Shear Strength:</b>                       | 5000 Single Pounds Per Square Inch                 |
| <b>Heat Treatment:</b>                       | Annealed Overall                                   |
| <b>Material:</b>                             | Titanium Alloy Uns R58450 Overall                  |
| <b>Material Document And Classification:</b> | Ams 4982 Assn Std Single Material Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.