

**Description**

MS20470T5-9 Solid Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470T59
Minimum Qty (MOQ):	10
NSN:	5320-00-170-3563
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



NO IMAGE  
AVAILABLE

## P/N MS20470T5-9 Specifications

<b>Fastener Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Shear Strength:</b>	50000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	-172,fscm 11815 Mfr Ref Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T5-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.