

Description

Fastener Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470T6145
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-249-8147
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N MS20470T6-14-5 Specifications

Fastener Length:	0.896 Inches Minimum And 0.916 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Shear Strength:	50000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Titanium Alloy Uns R58450 Overall
Material Document And Classification:	Ams 4982 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T6-14-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.