

**Description**

Fastener Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470T6145
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-249-8147
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

## P/N MS20470T6-14-5 Specifications

<b>Fastener Length:</b>	0.896 Inches Minimum And 0.916 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Shear Strength:</b>	50000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Titanium Alloy Uns R58450 Overall
<b>Material Document And Classification:</b>	Ams 4982 Assn Std Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470T6-14-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.