

# P/N MS20470T6-4

### **Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS20470T64

Minimum Qty (MOQ): 20 EA

NSN: 5320-00-170-3584

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470T6-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Shear Strength:	50000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Titanium Alloy Overall
Material Document And Classification:	-172,fscm 11815 Mfr Ref Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470T6-4">https://military-fasteners.com/rivets/solid+rivets/MS20470T6-4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.