

P/N MS20500-918

Description

Thread Size: 1/2", Nut Height: 3/4", Head Width: 7/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS20500918 |
|-------------------------|--|
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5310-00-995-9795 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093480, Bolts / Nuts Metal Silver Plated |



^{*} See page 2 for technical characteristics

P/N MS20500-918 Specifications

| Thread Class: | 3b |
|--|--|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Nut Style: | Hexagon |
| Nut Height: | 0.684 Inches Minimum And 0.704 Inches Maximum |
| Width Across Flats: | 0.865 Inches Minimum And 0.877 Inches Maximum |
| Temp Rating: | 1200.0 Deg Fahrenheit Nominal |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 18 |
| Nominal Thread Size: | 0.562 Inches |
| Bearing Surface Type: | Washer Faced |
| Material: | Steel Uns S34720 Overall Or Steel Uns S34723 Overall |
| Material Document And Classification: | Ams 5642 Assn Std All Material Responses Overall |
| Precious Material: | Silver |
| Surface Treatment: | Silver Overall |
| Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Overall |

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS20500-918 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.