

Description

Fastener Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20600AD5W9
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-046-5436
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20600AD5W9 Specifications

Fastener Length:	0.692 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Shear Strength:	580 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Body
Material:	Aluminum Alloy 2017 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20600AD5W9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.