

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20600M5W2
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-062-0621
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20600M5W2 Specifications

Fastener Length:	0.254 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	910 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Surface Treatment:	Any Acceptable Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20600M5W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.